

# ALED4T105Y/PCT



Specification grade area lights available in IES Type IV distributions. Suited for mounting on the sides of buildings and walls, and for illuminating the perimeter of parking areas. Replaces up to 400W metal halide. Patent pending management system. 5 Year Warranty.

Color: Bronze

Weight: 32.0 lbs

**Project:**

**Type:**

**Prepared By:**

**Date:**

#### Driver Info

Type:	Constant Current
120V:	0.89A
208V:	0.58A
240V:	0.50A
277V:	0.44A
Input Watts:	106W
Efficiency:	99%

#### LED Info

Watts:	105W
Color Temp:	3000K (Warm)
Color Accuracy:	81 CRI
L70 Lifespan:	100,000
Lumens:	8,461
Efficacy:	80 LPW

## Technical Specifications

<p><b>Other</b></p> <p><b>ALED4T105 with Photocell:</b> 120V-277V Photocell Twist</p> <p><b>Drivers:</b> Two Drivers, Constant Current, Class 2, 1400mA, 100-277V, 50/60Hz, 0.8A, Power Factor 99%</p> <p><b>California Title 24:</b> ALED4T105/PCT with the twistlock photocell option complies with 2013 California Title 24 building and electrical codes as a commercial outdoor pole-mounted fixture &gt; 75 Watts at mounting heights greater than 24 feet.</p> <p><b>Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.</p> <p><b>Country of Origin:</b> Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.</p> <p><b>Buy American Act Compliant:</b> This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.</p> <p><b>Recovery Act (ARRA) Compliant:</b> This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).</p> <p><b>Trade Agreements Act Compliant:</b> This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.</p> <p><b>GSA Schedule:</b> Suitable in accordance with FAR Subpart 25.4.</p>	<p><b>Listings</b></p> <p><b>UL Listing:</b> Suitable for wet locations.</p> <p><b>IESNA LM-79 &amp; LM-80 Testing:</b> RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have been received the Department of Energy "Lighting Facts" label.</p> <p><b>DLC Listed:</b> This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.</p> <p><b>Dark Sky Approved:</b> The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.</p> <p><b>LED Characteristics</b></p> <p><b>Lifespan:</b> 100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.</p> <p><b>LEDs:</b> Multi-chip, high-output, long-life LEDs</p> <p><b>Color Stability:</b> LED color temperature is warranted to shift no more than 200K in CCT over a 5 year period.</p> <p><b>Color Uniformity:</b> RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011.</p> <p><b>Construction</b></p> <p><b>IES Classification:</b> The Type IV distribution (also known as a Forward Throw) is especially suited for mounting on the sides of buildings and walls, and for illuminating the perimeter of parking areas. It produces a semiCircular distribution with essentially the same candlepower at lateral angles from 90° to 270°.</p>	<p><b>Effective Projected Area:</b> EPA = 0.75</p> <p><b>Ambient Temperature:</b> Suitable for use in 40°C (104°F) ambient temperatures.</p> <p><b>Cold Weather Starting:</b> The minimum starting temperature is -40°F/-40°C.</p> <p><b>Thermal Management:</b> Superior thermal management with external Air-Flow fins.</p> <p><b>Housing:</b> Die-cast aluminum housing, lens frame and mounting arm.</p> <p><b>Mounting:</b> Heavy-duty mounting arm with "O" ring seal &amp; stainless steel screws</p> <p><b>Reflector:</b> Specular vacuum-metallized polycarbonate</p> <p><b>Gaskets:</b> High-temperature silicone gaskets</p>
--	--	---

## Technical Specifications (continued)

<p><b>Construction</b></p> <p><b>Finish:</b> Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.</p> <p><b>Green Technology:</b> Mercury and UV free, and RoHS compliant. Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.</p>	<p><b>For use on LEED Buildings:</b> IDA Dark Sky Approval means that this fixture can be used to achieve LEED Credits for Light Pollution Reduction.</p> <p><b>Electrical</b></p> <p><b>THD:</b> 7.6% at 120V, 16.2% at 277V</p>	<p><b>Surge Protection:</b> 4kV</p> <p><b>Optical</b></p> <p><b>BUG Rating:</b> B1 U0 G2</p>
--	---	--

# ALED4T105Y/PCT



## Dimensions



## Features

- 66% energy cost savings vs. HID
- 100,000-hour LED lifespan
- Type IV distribution
- 5-year warranty

## Ordering Matrix

Family	Distribution	Watts	Mount	Color Temp	Finish	Voltage	Photocell	Dimming	Bi-Level
ALED									
	2T = Type II	150 = 150W	= Arm	= Cool	= Bronze	= 120-277V	= No Photocell	= No Dimming	= No Bi-Level
	3T = Type III	125 = 125W	SF = Slipfitter	Y = Warm	W = White	/480 = 480V	/PC = 120V Button	/D10 = Dimmable	/BL = Bi-Level
	4T = Type IV	105 = 105W		N = Neutral	RG = Gray		/PC2 = 277V Button		
							/PCS = 120V Swivel		
							/PCS2 = 277V Swivel		
							/PCT = 120-277V Twistlock		
							/PCS4 = 480V Swivel		
							/PCT4 = 480V Twistlock		