# EX12-3/4



Color: N/A

# **Technical Specifications**

# Construction

# Housings:

Heavy cast aluminum. Unit withstands 1490 lbs. per square inch hydrostatic pressure.

## Globe:

Impact and heat resistant clear prismatic design affords excellent light control.

# Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

## **Reflectors:**

Heavy gauge aluminum with highly reflective white acrylic finish.

## Hub Size:

3/4".

# Hub Count:

4

# Weight:

11 lb / 5 kg.

Electrical

# Wiring:

Wiring is factory sealed. Inspection hole provides easy access to splice compartment.

# Socket:

Medium base glazed porcelain. Leads pass through sealing compound that separates lamp chamber from wiring compartment. Heavy gauge nickel plated copper components. Spring loaded center contact.

# Other

Refer to the catalog for Class and Division specifications:

# Guard not supplied:

#### **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### **Project:** Type: **Prepared By:** Date: Lamp Info **Ballast Info** PS-25 Type: N/A Type: Watts: 300W 120V: N/A 208V: Shape/Size: N/A N/A 240V: N/A Base: N/A ANSI: N/A 277V: N/A Input Watts: Hours: N/A 0W Lamp Lumens: N/A Efficacy: N/A

#### **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

## **Recovery Act (ARRA) Compliant:**

This product complies wit the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

### Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

#### **GSA Schedule:**


This product is suitable for listing on the GSA Schedule of the US General Services in accordance with FAR Subpart 25.4.



# EX12-3/4



# Dimensions



# Features

Fixture comes complete with built-in junction box

Cast aluminum construction with gray polyester powder coat finish

Easy relamping with a single thumb screw

Factory sealed for easy installation

Heat and impact resistant prismatic glass globe

Die cast guard

Easy field installation