

LANDSCAPE Dome Top LAWN LIGHTS



Great new look for Landscape Lighting!
Features 2 level cutoff protection.
Now with Energy Saving CFL and
Self-Ballasted Fluorescent.



Rugged die cast aluminum housing
with durable powder coating.


Socket with all copper electrical parts and 20" leads

Quick and secure installation with one
corrosionproof screw

Threaded, gasketed globes for durable
weatherproofing and easy relamping

12" color matched mounting stem
with 1/2" threads available

Includes easy mounting 1/2" threaded nipple



2 Level Light Cutoff




Wide light spread for wider walkways & parking
lots where maximum light is required



Full Cutoff for narrow walkways & glare free
lighting in garden areas

Quick and Easy Adjustment



Product Information

Incandescent (120 volt)
Lamp not supplied

Compact Fluorescent (120 volt)
Lamp supplied with fixture.
Minimum operating temperature 32°
NPF 120 volt ballast

**Self Ballasted Compact
Fluorescent Lamps**
Lamp supplied with fixture
Minimum operating temperature -20°F

Lamp Watts	Lamp Type	Lamp Base	Initial Lumens	Lamp Hours
75	A-19	Med	1220	750
100	A-19	Med	1650	750
13	Quad	GX23-2	860	10,000
13	Spiral	Med	870	10,000
23	Spiral	Med	1450	10,000

Specifications

UL Listing:
Suitable for wet locations. Suitable for
mounting within 4 feet of the ground.

Socket:
Medium base porcelain with all copper
electrical parts and 20" leads, including
a ground lead.

Lamps:
Incandescent- (not supplied)
Medium base A-19 lamps, 120V.
4-tier - 100 watt max.
3-tier - 75 watt max.

Fluorescent- (supplied)
13 watt quad tube, GX23-2 base
13w self ballasted spiral lamp, Med. base
23w self ballasted spiral lamp, Med. base

Globes:
Threaded, gasketed globe protects against
weather, garden sprinklers and insects.
Clear glass GL100 globes standard for 4
Tier. Clear glass GL60 globes standard for
3 Tier.

Housing:
Die cast aluminum housing with powder
coat finish.

Voltage:
120 volts AC

Patents:
The designs of RAB fixtures are protected
under U.S. and international intellectual
property laws.

Replacement Parts:

Part	Catalog #
Socket	SLL
Globe for 4 tier -clear	GL100 (clear)
Globe for 4 tier -white	GL100W
Globe for 3 tier - clear	GL60

Mounting Stem:
Accessory 12" mounting stem with 1/2"
threads on both ends available

Part	Catalog #
12" Stem Verde Green	ST12VG
12" Stem Black	ST12B

Mighty Post Mounting:
See page 116.

Info Online 24/7



www.rabweb.com
Wiring Diagrams
Installation Instructions
Product Specifications

New!

Three Tier DomeTop

Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. Incandescent not supplied, Fluorescent supplied.

Finish: ● Black
● Verde Green



New!

Four Tier DomeTop

Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 -100 watt max. Incandescent not supplied, Fluorescent supplied.

Finish: ● Black
● Verde Green




Catalog Numbers

Verde Green	Black
LLD3VG	LLD3B
LLD3VG/F13	LLD3B/F13
LLD3VG/FS13	LLD3VG/FS13

Verde Green	Black
LLD4VG	LLD4B
LLD4VG/F13	LLD4B/F13
LLD4VG/FS23	LLD4VG/FS23

Dimensions



Mounting Options



Mighty Post
Mighty Post in lengths from 17" - 25" with a sturdy ground stabilizer



Turtle Power Post
19" Mighty Post with Turtle In-Use Cover for outlets & switches