


# BLED12N-180

LED bollard with architectural quality and strength at an affordable price point. Square post and head. Available in 12, 18 and 24 Watt versions that provide 90, 180, 270 and 360 degree lighting patterns.

Color: Bronze

Weight: 21.8 lbs



## LED Info

Watts: 12W  
 Color Temp: 4000K (Neutral)  
 Color Accuracy: 83  
 L70 Lifespan: 100000  
 LM79 Lumens: 560  
 Efficacy: 37 LPW

## Driver Info

Type: Constant Current  
 120V: 0.13A  
 208V: 0.09A  
 240V: 0.08A  
 277V: 0.07A  
 Input Watts: 15W  
 Efficiency: 78%

## Technical Specifications

### UL Listing:

Suitable for wet locations.

### LEDs:

6W multi-chip, long-life LEDs

### Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

### Driver:

Constant Current, Class2, 100-277V, 50/60 Hz, 4kV Surge Protection, 100-240VAC 0.3-0.15 A, 277VAC 0.3 A.

### THD:

10.9% at 120V

### Ambient Temperature:

Suitable for use in 40°C (104°F) ambient temperatures

### Cold Weather Starting:

Minimum starting temperature is -40°F/-40°C

### Thermal Management:

Cast aluminum Thermal Management system for optimal heat sinking. The BLED is designed for cool operation, maximum efficiency and long life by minimizing LED junction temperature.

### Housing:

Die-cast aluminum with extruded aluminum bollard shaft

### Lens:

Clear, vandal-resistant polycarbonate

### Mounting:

Four (4) anchor bolts provided for concrete pad mounting. Internal base support has leveling screws.

### Reflector:

Specular polycarbonate

### Gaskets:

High-temperature silicone gaskets seal out moisture

### Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

### Color Stability:

LED color temperature is warranted to shift no more than 200K in CCT over a 5 year period.

### Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011

### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contain no VOC or toxic heavy metals.

### Green Technology:

Mercury and UV free, and RoHS compliant. Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

### California Title 24:

BLED12 complies with 2013 California Title 24 building and electrical codes as a commercial outdoor non-pole-mounted fixture < 30 Watts when used with a photosensor control. Select catalog number PCS900(120V) or PCS900/277 to order a photosensor.

**IESNA LM-79 & IESNA LM-80 Testing:**

RAB LED fixtures have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

**Patents:**

The design of BLED is protected by patents pending in US, Canada, China, Taiwan and Mexico.

**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

**Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

**Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

**Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

**Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

**GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.