



	NAME:
300	

DATE:

TYPE:

DESCRIPTION

New! 3 Tier Dome Top offers wide light spread for wider walkways and Full Cutoff for narrow walkways and glare free lighting in garden area. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. incandescent, 13 watt fluorescent.

SPECIFICATIONS

Globes:

Threaded, gasketed globe protects against weather, garden sprinklers and insects. Clear glass GL 100 globes standard for 4

Tier. Clear glass GL60 globes standard for 3 Tire. GL100 white globes also available for attractive appearance and glare reduction.

Housing:

Die cast aluminum housing with powder coat base A-19 lamps, 120V. 75 watt max. finish

Mounting Stem:

Accessory 12" mounting stem with 1/2" threads on both ends available

Socket:

Medium base porcelain with all copper electrical parts and 20" leads, including a ground lead.

UL Listina:

Suitable for wet locations. Suitable for mounting within 4 feet of the ground

Voltage:

120 volts AC

Dome Top:

Wide light spread for wider walkways & parking lots where maximum light is required. Full Cutoff for narrow walkways & glare free lighting in garden areas.

Lamp:

Incandescent lamp not supplied. Medium

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Two Level Light Cutoff:

New Dome Top can adjust to Full Cutoff for narrow walkways and glare free lighting in garden areas by removing one tier

Color: Black Weight: 3.75

ORDERING INFORMATION

Total	Lamp	Lamp	Starting Amps/ Operating Amps					Input	LAMP	Initial	Lamp
Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
75	A-19	Medium	0	0	0	0	0	0		1220	750

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2009