

RAB LIGHTING LLD4B



JOB NAME: _____
 DATE: _____
 TYPE: _____

DESCRIPTION

New! 4 Tier Dome Top offers wide light spread for wider walkways and parking lots where maximum light is required. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. incandescent, 13 watt fluorescent.

SPECIFICATIONS

Globes:

Threaded, gasketed globe protects against weather, garden sprinklers and insects. Clear glass GL 100 globes standard for 4 Tier. Clear glass GL60 globes standard for 3 Tier. GL100 white globes also available for attractive appearance and glare reduction.

Housing:

Die cast aluminum housing with powder coat finish

Mounting Stem:

Accessory 12" mounting stem with 1/2" threads on both ends available

Socket:

Medium base porcelain with all copper electrical parts and 20" leads, including a ground lead.

Voltage:

120 volts AC

UL Listing:

Suitable for wet locations. Suitable for mounting within 4 feet of the ground

Dome Top:

Wide light spread for wider walkways & parking lots where maximum light is required. Full Cutoff for narrow walkways & glare free lighting in garden areas.

Lamp:

Incandescent lamp not supplied. Medium base A-19 lamps, 120V. 100 watt max.

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color:

Black

Weight:

4.35

ORDERING INFORMATION

Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
				120V	208V	240V	277V				
100	A-19	Medium	0	0	0	0	0	0		1650	750

Factory Installed Options

Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com
 © 2009