

# RWLED2T78N/BL

LED roadway lighting that's easy to buy. Free trial program and leasing options make it easy to get started with LED. Specification-grade optics deliver efficient, clean, uniform light distributions at a reasonable cost. Optics are factory installed and meet IES Lateral Distribution Type II.

Color: Bronze


Weight: 33.0 lbs

## LED Info

Watts: 78W  
 Color Temp: 4000K (Neutral)  
 Color Accuracy: 87  
 L70 Lifespan: 100000  
 LM79 Lumens: 4,284  
 Efficacy: 47 LPW

## Driver Info

Type: Constant Current  
 120V: 0.78A  
 208V: 0.50A  
 240V: 0.44A  
 277V: 0.38A  
 Input Watts: 90W  
 Efficiency: 86%



## Technical Specifications

### UL Listing:

Suitable for wet locations as a downlight.

### Bi-Level Operation:

Allows 33%-66%-100% output modes.

### Lumen Maintenance:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

### IES Classification:

The Type II distribution is ideal for entrance roadways, collector roads and other long, single-sided and narrow lighting applications. This type of lighting is commonly found on smaller local streets.

### Effective Projected Area:

EPA = 0.75

### IP Rating:

Ingress Protection rating of IP66 for dust and water.

### Vibration Rating:

Industry-leading 5G vibration rating per ANSI C136.31.

### LEDs:

Six (6) multi-chip, 13W, high-output, long-life LEDs.

### Drivers:

Three drivers, constant current, Class 2, 100 - 277V, 50 - 60 Hz, 100 - 277VAC:0.4 Amps

### THD:

13.7% at 120V

### Surge Protection:

6kV surge suppression protection tested in accordance with IEEE/ANSI C62.41.2.

### Ambient Temperature:

Suitable for use in 40°C ambient temperatures.

### Cold Weather Starting:

The minimum starting temperature is -40°F/-40°C.

### Thermal Management:

Superior patent pending thermal management design with external Air-Flow fins provides maximum operational life, even in high ambient temperature environments.

### Housing:

Die cast aluminum housing, lens frame and mounting arm.

### Mounting:

Fits most standard roadway upsweep arms. Adaptor brackets supplied fit 1", 1 1/4", 1 1/2" and 2" OD arms.

### Wedge Mounting Option:

Allows field adjustment of +/- 5 degree tilt to achieve a level installation of LROAD78 universal adaptor roadway fixtures. Wedge Mounting available .

### Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

### Color Stability:

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period.

### Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011.



Tech Help Line: 888 RAB-1000

Email: [sales@rabweb.com](mailto:sales@rabweb.com)

On the web at: [www.rabweb.com](http://www.rabweb.com)

**Reflector:**

Specular aluminum

**Gaskets:**

High temperature silicone gaskets

**Finish:**

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

**Green Technology:**

Mercury and UV free, and RoHS compliant. Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

**IESNA LM-79 & IESNA LM-80 Testing:**

RAB LED fixtures have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

**Replacement:**

The LROAD™ replaces 175W Mercury Vapor, 150W HPS/MH roadway fixtures.

**California Title 24:**

LROAD™ complies with California Title 24 building and electrical codes.

**Dark Sky Approved:**

The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.

**Patents:**

The LROAD™ design is protected by patents pending in the U.S., Canada, China, Taiwan and Mexico.

**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. See our full warranty .

**Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

**Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

**Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

**Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

**GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.

