



LOS2500/277



JOB NAME: _____
 DATE: _____
 TYPE: _____

DESCRIPTION

360° view Super Ceiling Sensor with Triple Overlapping Coverage for super sensitivity. Integral 30 amp power pack. No extra wires to run or extra boxes to install. Covers 2152 sf @ 9' height.

SPECIFICATIONS

Easy Installation:

Relay and sensor all in one reduces installation cost. Compatible with dimmers and electronic ballasts. LED testing and operation indicator.

Maximum Reliability:

Adjustable detector sensitivity for superior detection.

Maximum Versatility:

Adjustable time delay. Sensor detection pattern can be customized. No minimum load requirement. Can be wired in parallel.

UL Listing:

For indoor applications. Tuff Dome & Smart Box are UL Listed for wet locations.

Adjustments:

Photo Time Sensitivity

Coverage Area:

2152sf @ 9'

Detection:

360° view Super Ceiling Sensor

Fluorescent Watts Switched:

1500 watts

Incandescent Watts Switched:

1500 watts

Manual Switch:

None

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Power Consumption:

Negligible

Ratings Amps Horsepower:

16 amps 6.7 horsepower

Time Delay:

10 seconds to 15 minutes


Color:

White


Weight:

0.6

DIMENSIONS



DETECTION PATTERN



Note: Specifications may change without notice