



# LU300



JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

## DESCRIPTION

Luminator sensor with two weatherproof, corrosionproof floodlights and round mounting plate. PRE-WIRED FOR EASY INSTALLATION. Both floods and sensor have universal ball swivels for easy tool-less adjustment. Lamps not supplied.

## SPECIFICATIONS

### Auto Test Logic:

5 minutes of test time when power is turned on, Rests to auto mode without further adjustment

### Detector Sensitivity:

Adjustable from 100% to 50%

### Floodlights:

Made of tough, corrosion-resistant polycarbonate. Accepts PAR-38 lamps, medium base, 150 watts max. Lamps not included.

### Photo Control:

Deactivates lights during daylight

### Power Consumption:

1 watt

### Sensor Housing:

Made of tough, corrosion resistant polycarbonate

### Surge Protection:

Withstands up to 3000 volts

### Time Adjustment:

8 seconds to 10 minutes

### UL Listing:

Suitable for wet locations.

### Voltage:

120 volts AC 60 Hz.

### Wall Switch Manual Override:

Two flip logic prevents activation by momentary power outages. Override resets to auto after 6 hours or at dawn. No extra wiring needed.

### Detection:

110° view

### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

### Switching Capacity:

300 watts incandescent @ 120 volts, 2.5 amps

### Color:

Bronze

### Weight:

1.24

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com

© 2009