



## DESCRIPTION

Motion activated task light. 21" long, 13 watt fixture with integrated 180° view sensor that swivels 330°. Sensor can control up to 250 watts fluorescent. Lamps supplied.

## **SPECIFICATIONS**

Detection Zone: 120° by 30', aimable Fixture Finish: Bright white epoxy powder coating

Fixture Housing: Formed sheet metal with translucent styrene lens

### Fixture Sockets:

Miniature bi-pin, G5

Lamps Supplied: T5

Sensor Construction: Precision molded Lexan

#### Sensor Wires: 12" long

**Time Adjustment:** Adjustable from 5 seconds to 15 minutes

#### UL Listing:

For indoor applications.

Vandal Resistant Lens: Hard lens resists vandalism Voltage: 120 volts AC, 60 Hz

#### Wall Switch Manual Override:

Two flip logic prevents activation by momentary power outages. Override resets to auto at dawn. No extra wiring needed.

# Detection: 180° degree view


## Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Switching Capacity: 500 watts Incandescent or 250 watts Fluorescent

Color: White
Weight:
1.67

#### DIMENSIONS



## ORDERING INFORMATION

Fluorescent Lamp supplied with fixture	Total Lamp Lamp ixture Watts Type Base		Ballast	Starting 120V	g Amps/ O 208V	perating / 240V	Amps 277V	Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours	
	13	T5	Min	NPF 120V					0		870	7500
			Bi-Pin,									
Factory Installed Options			G4									

Add suffix to Catalog Number

Note: Specifications may change without notice

**RAB Lighting, Inc.** • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2009