



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Sensor controlled Vandalproof fixtures. VAN 3 up to 42 watts CFL. VAN5 up to 96 watts CFL, VAN6 up to 26 watts CFL @ 120v. Sensor color matched to fixture. Sensor is not vandalproof. Lamps supplied.

SPECIFICATIONS

"No Hands" Auto Testing:

Auto mode starts after 4 minutes of testing. No adjustment needed.

Built for Severe Conditions:

Double weatherproofing for long life

LED Detection Indicator:

Glows red day and night for "on-guard" deterrence.

Manual Override:

Double flip wall switch logic prevents activation by short power outages. Resets after 8 hours. No extra wiring needed.

Photocontrol:

Deactivates lights during daylight. Fully adjustable for 24 hour operation or custom applications. Please specify voltage.

Quick Test Time:

5 seconds test time for fast installation. Works day or night.

Sensor Case Construction:

Precision molded Lexan®

Surge Protection:

Withstands up to 3000 volts

Time Adjustment:

5 seconds to 15 minutes CFL lamps have longer life if Time Adjustment is set to < 7 minutes.

UL Listing:

Suitable for wet locations.

Vandal Resistant Lens:

Hard lens resists vandalism

Voltage:

120 volts AC 60 Hz.

Ballast Minimum Starting Temperature:

-22

Min Start Temp

0°

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

Color:

White

Weight:

7

ORDERING INFORMATION

Compact Fluorescent	Total	Lamp	Lamp		Starting Amps/ Operating Amps				Input	LAMP	Initial	Lamp
Lamp supplied with fixture	Watts	Type	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
	26	26W Triple	GX24q-3	Electronic QT	0.24	0.2	0.18	0.11	29		1800	12000

Factory Installed Options Add suffix to Catalog Number