

	NAME:	
JOD	INAIVIE.	

DATE:

TYPE:

## DESCRIPTION

Sensor controlled Vandalproof fixtures. VAN 3 up to 42 watts CFL. VAN5 up to 96 watts CFL, VAN6 up to 26 watts CFL @ 120v. Sensor color matched to fixture. Sensor is not vandalproof. Lamps supplied.

# SPECIFICATIONS

**"No Hands" Auto Testing:** Auto mode starts after 4 minutes of testing. No adjustment needed.

Built for Severe Conditions: Double weatherproofing for long life

### LED Detection Indicator:

Glows red day and night for "on-guard" deterrence.

### Manual Override:

Double flip wall switch logic prevents activation by short power outages. Resets after 8 hours. No extra wiring needed.

### Photocontrol:

Deactivates lights during daylight. Fully adjustable for 24 hour operation or custom applications. Please specify voltage.

### Quick Test Time:

5 seconds test time for fast installation. Works day or night.

#### Sensor Case Construction:

Precision molded Lexan®

Surge Protection: Withstands up to 3000 volts Time Adjustment: 5 seconds to 15 minutes CFL lamps have longer life if Time Adjustment is set to < 7 minutes. UL Listing:

Suitable for wet locations.

Vandal Resistant Lens: Hard lens resists vandalism

Voltage: 120 volts AC 60 Hz.

Ballast Minimum Starting Temperature:

Min Start Temp:

0° Patents: Pat. D547,484 Color: Bronze Weight: 11.5

## ORDERING INFORMATION

Compact Fluorescent Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps 120V 208V 240V 277V				Input Watts	LAMP ANSI	P Initial Lumens	Lamp Hours
Factory Installed Options	96	3 - 32W Triple	GX24q-3	Electronic QT	0.88	0.7	0.6	0.38	108		7200	12000

Add suffix to Catalog Number

Note: Specifications may change without notice

**RAB Lighting, Inc.** • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com