



# VANGS150QT/PC

JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

## DESCRIPTION

15" round die cast aluminum housing with vandalproof refractor for optimum parking garage light distribution. 150 or 175 w vertical mount Metal Halide or 100,000 hour Induction Lamp supplied.

## SPECIFICATIONS

### Fluorescent Ballast Starting Temperatures: Sockets:

Electronic QT: 0° F/ -18° C NPF 120V:  
32° F / 0° C

HPS & MH: Medium base 4kv Pulse Rated  
Glazed porcelain CFL: Plug-in type,  
thermoelastic  
UL Listing.

### Housings:

Die cast aluminum with powder coat bronze or white finish

Suitable for wet locations. Fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

### Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

### HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure

### Refractor:

Injection molded polycarbonate, designed for maximum structural strength

### Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER)

### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

### Color:

Bronze

### Weight:

21

## ORDERING INFORMATION

High Pressure Sodium Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	150	ED17	Medium	HX-HPF QT	2.0/1.7	1.2/1.0	1/1.9	.9/.8	188	S55	16000	24000
<b>Factory Installed Options</b> Add suffix to Catalog Number				Swivel Photocontrol (/PCS) Quartz Restrike (HPS & MH only) (/QR)								
												Mini Motion Sensor (/MS) Button Photocontrol (/PC)

Note: Specifications may change without notice