



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Large size fixture: 150 watt (2x75w) incandescent. Reflector is die formed heavy gauge steel in white finish with clear polycarbonate refractor. Lamp not supplied.

SPECIFICATIONS

Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

Refractor:

Injection molded polycarbonate, designed for maximum structural strength

Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER)

Sockets:

Plug-in type, thermoplastic

UL Listing:

Suitable for wet locations. Fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

Photocontrol:

Button Photocontrol requires mounting back box. Product number VAN4BB

Color:


Clear

Weight:

5.16


Mini Motion Sensor (/MS)

DIMENSIONS



PHOTOMETRIC

150w Incandescent @ 8' Mounting Height



ORDERING INFORMATION

Incandescent Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting 120V	Amps/ O 208V	perating A 240V	mps 277V	Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
	150	2-75w A-19	Medium						0		2420	750
Factory Installed Options	Swivel F	Photocontro	ol (/PCS)		Button F	hotocontro	ol (Require	s Mounting	Back Box)	(/PC)		

Note: Specifications may change without notice

Add suffix to Catalog Number