

JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Large size ceiling mount fixture: Horizontal CFL lamps. "No Bend" conduit entrance. Housing is die cast aluminum with clear vandalproof polycarbonate refractor. Lamps supplied.

SPECIFICATIONS

HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure

Housings:

Die cast aluminum with powder coat bronze or white finish

Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

Refractor:

Injection molded polycarbonate, designed for maximum structural strength

Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER)

Sockets:

Medium base 4kv Pulse Rated Glazed porcelain

UL Listing:

Suitable for wet locations. Fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

Ballast Minimum Starting Temperature: 0

Patents:


The unique RAB VAN5 is protected by U.S. Patent D547,484; China Patent ZL200630133218.0: Taiwan Patent D121,295 and Canada Patent D115,523

Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts


Color: Bronze Weight: 10.5

DIMENSIONS



PHOTOMETRIC

150w HPS @ 8' Mounting Height



Mounting Height Multiplier		Watts	Multiplier HPS MH CF					
8'	1.0	64			.3			
9'	.8	84			.4			
10'	.7	96			.5			
12'	.4	100	.6	.6				
14'	.3	150	1.0	.8				
		175		.9				

ORDERING INFORMATION

Compact Fluorescent	Total Lamp		Lamp		Starting Amps/ Operating Amps			Input	LAMP	Initial	Lamp	
Lamp supplied with fixture	Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
	96	3 - 32W	GX24q-3	Elec HPF QT	0.88	0.7	0.6	0.38	108		7200	12000
Factory Installed Options Add suffix to Catalog Number					otion Senso Photocontr	()						

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2009