

OB NAME:	
DATE:	
TYPF:	

DESCRIPTION

Large size ceiling mount fixture: Increased wattage to 200W MH PS. Vertical lamp HID. Adjustable, 4-way glare guard & "No Bend" conduit entrance. Excellent heat control eliminates heat problems. Housing is die cast aluminum with clear vandalproof polycarbonate refractor. Lamps supplied.

SPECIFICATIONS

HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure

Housings:

Die cast aluminum with powder coat bronze or white finish

Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

Refractor:

Injection molded polycarbonate, designed for maximum structural strength

Sockets:

Medium base 4kv Pulse Rated Glazed porcelain

Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER)

UL Listing:

Suitable for wet locations. Fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

Patents

The unique RAB VAN5 is protected by U.S. Patent D547,484; China Patent ZL200630133218.0; Taiwan Patent D121,295 and Canada Patent D115,523.


Color:

Bronze


Weight:

12.5

DIMENSIONS



PHOTOMETRIC



Mounti Height	ng Multiplier	Multiplier Watts HPS MH CFL							
8'	1.0	64	0		.3				
9'	.8	84			.4				
10'	.7	96			.5				
12'	.4	100	.6	.6					
14'	.3	150	1.0	.8					
		175		.9					

ORDERING INFORMATION

High Pressure Sodium Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting 120V	g Amps/ C 208V	perating A	Amps 277V	Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
2.1.2.11	100	FD17	Medium	R-NPF 120V	3 1/2 1				115	S54	9500	24000

 Factory Installed Options
 Swivel Photocontrol (/PCS)
 Mini Motion Sensor (/MS)

 Add suffix to Catalog Number
 Quartz Restrike (HPS & MH only) (/QR)
 Button Photocontrol (/PC)

Note: Specifications may change without notice