

JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Large size ceiling mount fixture: Increased wattage to 200W MH PS. Vertical lamp HID. Adjustable, 4-way glare guard & "No Bend" conduit entrance. Excellent heat control eliminates heat problems. Housing is die cast aluminum with clear vandalproof polycarbonate refractor. Lamps supplied.

SPECIFICATIONS

HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure

Housings:

Die cast aluminum with powder coat bronze or white finish

Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

Refractor:

Injection molded polycarbonate, designed for maximum structural strength

Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER)

Sockets:

Medium base 4kv Pulse Rated Glazed porcelain

UL Listing:

Suitable for wet locations. Fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

Patents:

The unique RAB VAN5 is protected by U.S. Patent D547,484; China Patent ZL200630133218.0; Taiwan Patent D121,295 and Canada Patent D115,523.

Photocontrol:

Button Photocontrol installed and wired for $120 \ensuremath{\mathsf{V}}$


Quad Tap:

Fixture works with 120, 208, 240, and 277 volts

Color: White Weight:


16

DIMENSIONS



PHOTOMETRIC

150w HPS @ 8' Mounting Height



Mounti Height	ng Multiplier	Watts	Multij HPS	olier MH	CFL
8'	1.0	64			.3
9'	.8	84			.4
10'	.7	96			.5
12'	.4	100	.6	.6	
14'	.3	150	1.0	.8	
		175		.9	

ORDERING INFORMATION

High Pressure Sodium	Total Lamp Lamp		Starting Amps/ Operating Amps				Input	LAMP	Initial	Lamp		
Lamp supplied with fixture	Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
	150	ED17	Medium	HX-HPF QT	2/1.7	1.2/1.0	1/.9	.9/.8	188	S55	16000	24000
Factory Installed Options Add suffix to Catalog Number		Swivel Photocontrol (/PCS) Quartz Restrike (HPS & MH only) (/QR)			Mini Motion Sensor (/MS) Button Photocontrol (/PC)							

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com