

JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Versatile wall and ceiling fixture in 13 and 26 watt fluorescent. Housing is die cast aluminum bronze finish with clear vandalproof polycarbonate refractor. Photocontrol & sensor models available. Lamp supplied.

SPECIFICATIONS

HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure

Housings:

Die cast aluminum with powder coat bronze or white finish

Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

Refractor:

Injection molded polycarbonate, designed for maximum structural strength

Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER)

Ballast Minimum Starting Temperature: 32

Sockets:

HPS: Medium base 4kv Pulse Rated Glazed porcelain CFL: Plug-in type, thermoplastic

UL Listing:

Suitable for wet locations. Fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

F13:

Compact Fluorescent 13W

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.


Photocontrol:

Button Photocontrol installed and wired for 120V


Color: Bronze Weight:

4.6

DIMENSIONS







Multiplier HPS CFL .6 1.0

> .2 .4

			_
Mounti Height	Watts	s	
8'	1.0	35	
9'	.8	50	
10'	.7	13	
12'	.4	26	
14'	.3		

ORDERING INFORMATION

Compact Fluorescent	Total	Total Lamp		Lamp		Starting Amps/ Operating Amps			Input	LAMP	Initial	Lamp
Lamp supplied with fixture	Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
	13	13W Twin	GX23	NPF 120V	.4/.3				16		900	10000
Factory Installed Options Add suffix to Catalog Number		Photoconti Restrike (ł	()	only) (/QR)		ntion Senso Photocontr	()					

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com