



OB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Pendant mount, die cast aluminum construction. Medium base socket, 1/2" or 3/4" NPS pendant thread and a variety of globes.

SPECIFICATIONS

Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

UL Listing:

Suitable for wet locations. Suitable for use in Patents: dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

Colored Globe Maximum Watts:

150 watts

Die Cast Guard:

Supplied with one piece silver gray die cast guard with set screw

Maximum Watts:

200 watts

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.


Color:

Silver

Weight:

3.84

DIMENSIONS



ORDERING INFORMATION

Total Lamp Lamp				Starting Amps/ Operating Amps				Input	LAMP	Initial	Lamp	
Watts	Type	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours	_
200	A19	Medium	0	0	0	0	0	0	0	0	0	

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice