

OB NAME:	
DATE:	
TYPE:	

## **DESCRIPTION**

Box mount, die cast aluminum with built-in junction box and sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes.

# **SPECIFICATIONS**

#### Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

### **Colored Globe Maximum Watts:**

100 watts

**Hub Size:** 3/4" Tapped

No Guard Supplied

Color: Black

#### **UL Listing:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

#### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

## Weight:

2.5

# ORDERING INFORMATION

Total	Lamp	Lamp	St	Starting Amps/ Operating Amps					LAMP	Initial	Lamp		
Watts	Type	Base	Ballast	12	20V	208V	240V	277V	Watts	ANSI	Lumens	Hours	
150	A19	Medium	0	C	)	0	0	0	0	0	0	0	

**Factory Installed Options** Add suffix to Catalog Number

Note: Specifications may change without notice