

JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Small cast aluminum housing for 13 and 26 watt or larger size housing for 32 and 42 compact fluorescent. Prismatic globe for low glare and even light distribution. Fixture mounts to junction box or can be wired inside the housing. Ceiling mounted with 1/2" (or 3/4") side and top conduit feed. Lamp supplied.

SPECIFICATIONS

Construction:

Die cast aluminum with brass screws **Globes:**

Clear prismatic, heat resistant glass standard. White glass globes available. Colored and clear unbreakable RAB Permaglobes available for CFL only.

Guard:

One piece die cast aluminum with set screw **Optional Reflectors:**

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. **Socket:**

HID: Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts. CFL: White thermo plastic with integral clips for lamp retention.

UL Listing:

Suitable for wet locations. Complies with UL Standard 1598 for non-hazardous locations where the lamp, socket and wiring require protection from air, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

Ballast Minimum Starting Temperature: 0° F

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

Color:

Silver

Weight:

4.1

DIMENSIONS VX1F: 6" (15.2cm) VX2F: 6" (15.2cm)	
	9 3/4" 24.7 cm 9 3/4" 24.7 cm 9 3/4" 30.5 cm

ORDERING INFORMATION

Compact Fluorescent	Total La	Lamp Lamp		Starting Amps/ Operating Amps				Input	LAMP	Initial	Lamp	
Lamp supplied with fixture	Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
	32	32W Triple	GX24q-3	Elec HPF QT	0.31	0.2	0.2	0.13	32		2400	12000

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice