

JOB NAME:
DATE:
TYPE:

## **DESCRIPTION**

Cast aluminum housing with sturdy wall mounting bracket for 50, 70 & 100 watt HPS, 50, 70 & 100 watt Metal Halide. Prismatic globe for low glare and even light distribution. Fixture mounts to junction box or can be wired inside the housing. Wall mounted with 1/2" (or 3/4") side and top conduit feel. Lamp supplied.

## **SPECIFICATIONS**

### **Construction:**

Die cast aluminum with brass screws **Globes:** 

Clear prismatic, heat resistant glass standard. White glass globes available. Colored and clear unbreakable RAB Permaglobes available for CFL only.

#### Guard:

One piece die cast aluminum with set screw

#### **Optional Reflectors:**

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures

# Socket:

HID: Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts. CFL: White thermo plastic with integral clips for lamp retention.

#### **UL Listing:**

Suitable for wet locations. Complies with UL Standard 1598 for non-hazardous locations where the lamp, socket and wiring require protection from air, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

#### **Hub Size:**

3/4" Tapped

#### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

#### Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts


#### Color:

Natural

## Weight:

12.35

## **DIMENSIONS**



## ORDERING INFORMATION

High Pressure Sodium Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting 120V	Amps/ Op 208V	erating A	mps 277V	Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
	100	ED17	Medium	HX-HPF QT	1.3/1.2	.8/.7	.7/.6	.6/.5	130	S54	9500	24000

Factory Installed Options
Add suffix to Catalog Number