

| JOB NAME: |  |
|-----------|--|
| DATE:     |  |
| TYPE:     |  |
|           |  |

# DESCRIPTION

Cast aluminum housing with sturdy wall mounting bracket for 50, 70 & 100 watt HPS, 50, 70 & 100 watt Metal Halide. Prismatic globe for low glare and even light distribution. Fixture mounts to junction box or can be wired inside the housing. Wall mounted with 1/2" (or 3/4") side and top conduit feel. Lamp supplied.

# SPECIFICATIONS

## **Construction:**

Die cast aluminum with brass screws **Globes:** 

Clear prismatic, heat resistant glass standard. White glass globes available. Colored and clear unbreakable RAB Permaglobes available for CFL only.

## Guard:

One piece die cast aluminum with set screw

## **Optional Reflectors:**

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures

#### fixtures. Socket:

HID: Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts. CFL: White thermo plastic with integral clips for lamp retention.

## UL Listing:

Suitable for wet locations. Complies with UL Standard 1598 for non-hazardous locations where the lamp, socket and wiring require protection from air, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

# Hub Size:

# 3/4" Tapped

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

## Quad Tap:


Fixture works with 120, 208, 240 and 277 Volts

## Color:

## White

Weight: 11.85

# DIMENSIONS



# ORDERING INFORMATION

| High Pressure Sodium       | Total | Lamp | Lamp   |           | Starting Amps/ Operating Amps |       |       |       |       | LAMP | Initial | Lamp  |
|----------------------------|-------|------|--------|-----------|-------------------------------|-------|-------|-------|-------|------|---------|-------|
| Lamp supplied with fixture | Watts | Туре | Base   | Ballast   | 120V                          | 208V  | 240V  | 277V  | Watts | ANSI | Lumens  | Hours |
|                            | 70    | ED17 | Medium | HX-HPF QT | .8/.8                         | .5/.5 | .4/.4 | .4/.4 | 91    | S62  | 6300    | 24000 |

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2010 RAB Lighting, Inc.