

JOB NAME:	
DATE:	
TYPE:	

## **DESCRIPTION**

Cast aluminum housing with sturdy wall mounting bracket for 50, 70 & 100 watt HPS, 50, 70 & 100 watt Metal Halide. Prismatic globe for low glare and even light distribution. Fixture mounts to junction box or can be wired inside the housing. Wall mounted with 1/2" (or 3/4") side and top conduit feel. Lamp supplied.

# **SPECIFICATIONS**

## **Construction:**

Die cast aluminum with brass screws **Globes:** 

Clear prismatic, heat resistant glass standard. White glass globes available. Colored and clear unbreakable RAB Permaglobes available for CFL only.

#### Guard:

One piece die cast aluminum with set screw

## **Optional Reflectors:**

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures

Socket:

HID: Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts. CFL: White thermo plastic with integral clips for lamp retention.

#### **UL Listing:**

Suitable for wet locations. Complies with UL Standard 1598 for non-hazardous locations where the lamp, socket and wiring require protection from air, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

#### **Hub Size:**

3/4" Tapped

#### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws


## Color:

Natural

## Weight:

8.85

# **DIMENSIONS**



## ORDERING INFORMATION

**High Pressure Sodium** Total Lamp Lamp Starting Amps/ Operating Amps Input LAMP Initial Lamp 120V 240V Lamp supplied with fixture Watts Type **Ballast** Hours 100 ED17 Medium R-NPF 120V 3.1/2.1 S54 9500 24000

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice