

# VAPORPROOF WALL BRACKET FIXTURES

**Durable, versatile and economical vaporproof incandescent or fluorescent lighting for non-hazardous locations.**

Die cast aluminum for superior durability

Set screw keeps guard securely in place

Junction box with sturdy mounting lugs

All stainless steel hardware

Close-up plugs allow Phillips or slotted screwdrivers for easy installation

One piece die cast aluminum guards threaded for secure fit

High temperature silicone internal gaskets

Premium porcelain socket with 150°C 8" long leads attached

Clear heat resistant glass globes standard  
Polycarbonate Permaglobes available

Packed partially unassembled for easy installation

**New!**

UL Listed for use with 90°C supply wiring  
OK for use in dwellings and wet locations



*Durable Vaporproof fixtures light up entrances in industrial locations.*



*A VX100DG in a scene from the movie "Mystic Pizza" starring Julia Roberts. In Hollywood, they install fixtures upside down. You should always install fixture lamp base up.*



*Best Supporting Prop in a movie! Here's a RAB Vaporproof in a scene from Ron Howard's "The Paper" starring Michael Keaton and Glenn Close. (When using outdoors, always install lamp base up.)*

## Specifications

### UL Listing:

Suitable for wet locations.  
Suitable for use in dwellings.  
Suitable for use with 90°C supply wiring.  
Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

### Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

### Hub Size:

1/2" or 3/4" NPS. Metric size hub taps available. Consult factory.

### Construction:

Die cast aluminum with brass screws.

### Globes:

Clear heat resistant glass standard.  
Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in color. See page 162.

### Reflectors:

Customize fixture with a highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See page 164.

### Finish:

Natural unpainted finish standard. Painted finishes of Silver Gray (add suffix S), White (add W) and Black (add B). Other finish colors available. Consult factory.

### Guard:

One piece die cast aluminum with set screw.

### Wire Guard:

8 GA. steel wire with silver powder coat.

### Socket:

Incandescent: Premium porcelain with 150°C 8" leads attached. Fastened with 2 brass screws.

### CFL Lamp Base:

13w: G23-2 Base • 22w: GX32d-2 Base  
23w: Self Ballasted, Medium Base Spiral FL

### CFL Ballast:

NPF 120V

### Patents:

The configuration and design of RAB Vaporproof fixtures are a U.S. registered trademark and protected under U.S. and international intellectual property laws.



[www.rabweb.com](http://www.rabweb.com)

Wiring Diagrams  
Installation Instructions  
Product Specifications

## Special Globes

Colored (White, Red, Blue, Green or Amber) Prismatic or Ball shaped globes are available in glass or polycarbonate. Heat resistant glass globes are also available. Order a vaporproof fixture less globe and combine it with a Globe from Page 162.

### Glass



### Unbreakable Polycarbonate



## VBR Bracket

Die cast aluminum construction with sturdy wall mounting bracket. Medium base socket and a variety of globes. Incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied. CFL: 13, 22, 23 watt lamp supplied.

Finish:   
☐ Natural   
☐ Silver Gray   
☐ White   
☐ Black



VBR100DG  
shown in Natural

## VXBR Bracket & Box

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied. CFL: 13, 22, 23 watt lamp supplied.

Finish:   
☐ Natural   
☐ Silver Gray   
☐ White   
☐ Black



VXBR100DG  
shown in Natural

## Adjustable Pendant

Universal swivel permits mounting at any angle and locks in place. Die cast aluminum construction. Medium base socket and a variety of globes. Incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied. CFL: 13, 22, 23 watt lamp supplied.

Finish: ☐ Natural



VA100DG  
shown in Natural

## Product Information

### Natural Fixture with:

clear glass & die cast guard

clear glass & wire clamp guard

clear glass globe (no guard)

clear Perm globe (no guard)

white Perm globe (no guard)

Fixture less globe

13 watt Fluorescent, 120 Volt  
Lamp supplied

22 watt Fluorescent, 120 Volt  
Lamp supplied

23 watt Self Ballasted Fluorescent  
Lamp supplied

3/4" tapped hubs



**CFL**  
**SELF-BALLASTED**  
**CFL**

Finish:   
☐ Silver Gray   
☐ White   
☐ Black

Add suffix

## Catalog Numbers


100 Series	200 Series
Max Watts	Max Watts
150w Clear Glass	200w Clear Glass
100w Colored Glass	150w Colored Glass
75w Perm globe	100w Perm globe
VBR100DG	VBR200DG
VBR100G	VBR200G
VBR100	VBR200
VBR100P	VBR200P
VBR100PW	VBR200PW
VBR1	VBR2
add /F13	
	add /F22
add /FS23	
add S	add S
add W	add W
add B	add B
Natural, no suffix	

100 Series	200 Series
Max Watts	Max Watts
150w Clear Glass	300w Clear Glass
100w Colored Glass	200w Colored Glass
75w Perm globe	100w Perm globe
VXBR100DG	VXBR200DG
VXBR100G	VXBR200G
VXBR100	VXBR200
VXBR100P	VXBR200P
VXBR100PW	VXBR200PW
VXBR1	VXBR2
add /F13	
	add /F22
add /FS23	
add -3/4	add -3/4
add S	add S
add W	add W
add B	add B
Natural, no suffix	


100 Series	200 Series
Max Watts	Max Watts
150w Clear Glass	300w Clear Glass
100w Colored Glass	200w Colored Glass
75w Perm globe	100w Perm globe
VA100DG	VA200DG
VA100G	VA200G
VA100	VA200
VA100P	VA200P
VA100PW	VA200PW
VA1	VA2
add /F13	
	add /F22
add /FS23	
add -3/4	add -3/4

## Dimensions

VBR100DG & VBR200DG



VXBR100DG & VXBR200DG



VA100DG & VA200DG

