



# VBR100P



JOB NAME: \_\_\_\_\_  
 DATE: \_\_\_\_\_  
 TYPE: \_\_\_\_\_

## DESCRIPTION

Die cast aluminum construction with sturdy wall mounting bracket. Medium base socket and a variety of globes. Incandescent up to 200 watts. CFL 13 or 22 watts. Fits 4" box. CFL lamp supplied. Incandescent lamp not supplied.

## SPECIFICATIONS

### Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in color.

### Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

### Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

### UL Listing:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

### Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

### Globe:

Supplied with clear flat bottom prismatic polycarbonate globe. Not for use with diecast or wire guard.

### Maximum Watts:

75 watts

### Optional Guard:

Order flat bottom guard separately. CAT# GD100BAR

### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

### Color:

Natural

### Weight:

2.34

## ORDERING INFORMATION

| Total<br>Watts | Lamp<br>Type | Lamp<br>Base | Ballast | Starting Amps/ Operating Amps |      |      |      | Input<br>Watts | LAMP<br>ANSI | Initial<br>Lumens | Lamp<br>Hours |
|----------------|--------------|--------------|---------|-------------------------------|------|------|------|----------------|--------------|-------------------|---------------|
|                |              |              |         | 120V                          | 208V | 240V | 277V |                |              |                   |               |
| 75             | A19          | Medium       | 0       | 0                             | 0    | 0    | 0    | 0              | 0            | 0                 |               |

### Factory Installed Options

Add suffix to Catalog Number

Note: Specifications may change without notice