

# VBR200P-S

OB NAME:	
DATE:	
TYPE:	

## **DESCRIPTION**

Die cast aluminum construction with sturdy wall mounting bracket. Medium base socket and a variety of globes. Incandescent up to 200 watts. CFL 13 or 22 watts. Fits 4" box. CFL lamp supplied. Incandescent lamp not supplied.

## **SPECIFICATIONS**

#### Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in

## Color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

#### Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

### **UL Listing:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

#### Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

#### Globe:

Supplied with clear flat bottom prismatic polycarbonate globe. Not for use with diecast or wire guard.

## **Maximum Watts:**

100 watts

## **Optional Guard:**

Order flat bottom guard separately. CAT# GD200BAR

#### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

## Color:

Silver

## Weight:

2.5

## ORDERING INFORMATION

Total	Lamp	Lamp			Starting Amps/ Operating Amps				Input	LAMP	Initial	Lamp	
Watts	Type	Base	Ballast		120V	208V	240V	277V	Watts	ANSI	Lumens	Hours	
75	A19	Medium	0		0	0	0	0	0	0	0	0	

**Factory Installed Options** Add suffix to Catalog Number