

# VBR2S

| OB NAME: |  |
|----------|--|
| DATE:    |  |
| TYPE:    |  |

## **DESCRIPTION**

Die cast aluminum construction with sturdy wall mounting bracket. Medium base socket and a variety of globes. Incandescent up to 200 watts. CFL 13 or 22 watts. Fits 4" box. CFL lamp supplied. Incandescent lamp not supplied.

# **SPECIFICATIONS**

## Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in

# color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

### Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

### **UL Listing:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

# No Guard or Globe Supplied

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

### Color:

Silver

## Weight:

2.34

# ORDERING INFORMATION

| Total | Lamp | Lamp   |         |  | Starting Amps/ Operating Amps |      |      |      | Input | LAMP | Initial | Lamp  |
|-------|------|--------|---------|--|-------------------------------|------|------|------|-------|------|---------|-------|
| Watts | Type | Base   | Ballast |  | 120V                          | 208V | 240V | 277V | Watts | ANSI | Lumens  | Hours |
| 200   | A19  | Medium | 0       |  | 0                             | 0    | 0    | 0    | 0     | 0    | 0       | 0     |

**Factory Installed Options** Add suffix to Catalog Number