

JOB NAME:

DATE:

TYPE:

DESCRIPTION

Die cast aluminum construction with sturdy wall mounting bracket. Medium base socket and a variety of globes. Incandescent up to 200 watts. CFL 13 or 22 watts. Fits 4" box. CFL lamp supplied. Incandescent lamp not supplied.

SPECIFICATIONS

Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in color

color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

Ballast Minimum Starting Temperature: 32

UL Listing:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

F22:

Compact Fluorescent 22W

No Guard or Globe Supplied

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color: Natural Weight: 0

ORDERING INFORMATION

Compact Fluorescent	Total	Lamp	Lamp	Ballast	Starting	g Amps/ O	perating A	Amps	Input	LAMP	Initial	Lamp
Lamp supplied with fixture	Watts	Type	Base		120V	208V	240V	277V	Watts	Ansi	Lumens	Hours
	22	22W Quad	GX32d-2	NPF 120V	0.45				25		1200	10000

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2010 RAB Lighting, Inc.