Durable, versatile and economical vaporproof incandescent or fluorescent lighting for non-hazardous locations.

Die cast aluminum for superior durability

Set screw keeps guard securely in place

Junction box with sturdy mounting lugs

All stainless steel hardware



Close-up plugs allow Phillips or slotted screwdrivers for easy installation

One piece die cast aluminum guards threaded for secure fit

High temperature silicone internal gaskets

Premium porcelain socket with 150°C 8" long leads attached

Clear heat resistant glass globes standard Polycarbonate Permaglobes available

Packed partially unassembled for easy installation

w

UL Listed for use with 90°C supply wiring OK for use in dwellings and wet locations



Durable Vaporproof fixtures light up entrances in industrial locations.

Specifications 🖤

UL Listing:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

Hub Size:

1/2" or 3/4" NPS. Metric size hub taps available. Consult factory.

Construction:

Die cast aluminum with brass screws



Globes:

Clear heat resistant glass standard. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in color. See page 162.

Reflectors:

Customize fixture with a highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See page 164.

Finish:

Natural unpainted finish standard. Painted finishes of Silver Gray (add suffix S), White (add W) and Black (add B). Other finish colors available. Consult factory.

Guard:

One piece die cast aluminum with set screw.

Wire Guard: 8 GA. steel wire with silver powder coat.



A VX100DG in a scene from the movie "Mystic Pizza" starring Julia Roberts. In Hollywood, they install fixtures upside down. You should always install fixture lamp base up.



Best Supporting Prop in a movie! Here's a RAB Vaporproof in a scene from Ron Howard's "The Paper" starring Michael Keaton and Glenn Close. (When using outdoors, always install lamp base up.)

Special Globes

Colored (White, Red, Blue, Green or Amber) Prismatic or Ball shaped globes are available in glass or polycarbonate. Heat resistant glass globes are also available. Order a vaporproof fixture less globe and combine it with a Globe from Page 162.



Opal Clear Ruby Blue G



156



Incandescent: Premium porcelain with 150°C 8" leads attached. Fastened with 2 brass screws.

CFL Lamp Base:

13w: G23-2 Base • 22w: GX32d-2 Base 23w: Self Ballasted, Medium Base Spiral FL

CFL Ballast: **NPF 120V**

Patents:

The configuration and design of RAB Vaporproof fixtures are a U.S. registered trademark and protected under U.S. and international intellectual property laws.

www.rabweb.com

Wiring Diagrams Installation Instructions Product Specifications

VBR Bracket

Lamp not supplied.

Finish:

Die cast aluminum construction

100 Series, PS25 for 200 Series.

CFL: 13, 22, 23 watt lamp supplied.

Natural Silver Gray

O White

Black

VBR100DG

Catalog Numbers

shown in Natural

200 Series

200w Clear Glass

150w Colored Glass

Max Watts

with sturdy wall mounting bracket.

Medium base socket and a variety

of globes. Incandescent lamp A21 for

VXBR Bracket & Box

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied. CFL: 13, 22, 23 watt lamp supplied.

Finish: Natural Silver Gray ○ White Black

add /FS23

add -3/4

add S

add W

add B

Natural, no suffix

VXBR100DG sho

show	n in Natural	
100 Series <u>Max Watts</u> 150w Clear Glass 100w Colored Glass 75w Permaglobe	200 Series Max Watts 300w Clear Glass 200w Colored Glass 100w Permaglobe	100 Se <u>Max Wa</u> 150w Cl 100w Cc 75w Pe
VXBR100DG	VXBR200DG	VA100E
VXBR100G	VXBR200G	VA1000
VXBR100	VXBR200	VA100
VXBR100P	VXBR200P	VA100F
VXBR100PW	VXBR200PW	VA100F
VXBR1	VXBR2	VA1
add /F13		add /F13
	add /F22	

Adjustable Pendant

Universal swivel permits mounting at any angle and locks in place. Die cast aluminum construction. Medium base socket and a variety of globes. Incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied. CFL: 13, 22, 23 watt lamp supplied.



VA100DG shown in Natural

100 Series <u>Max Watts</u> 150w Clear Glass 100w Colored Glass 75w Permaglobe	200 Series Max Watts 300w Clear Glass 200w Colored Gla 100w Permaglobo
VA100DG	VA200DG
VA100G	VA200G
VA100	VA200
VA100P	VA200P
VA100PW	VA200PW
VA1	VA2
add /F13	
	add /F22
add /FS23	
add -3/4	add -3/4

Product Information

Natural Fixture with:
clear glass & die cast guard
clear glass & wire clamp guard
clear glass globe (no guard)
clear Permaglobe (no guard)
white Permaglobe (no guard)
Fixture less globe
13 watt Fluorescent, 120 Volt CFL
22 watt Fluorescent, 120 Volt Lamp supplied
Lamp supplied 23 watt Self Ballasted Fluorescent New Lamp supplied
3/4" tapped hubs

Silver Gray

White

Black

Finish:

Add suffix

	75WT CITILIGIODC
	VBR100DG
	VBR100G
	VBR100
	VBR100P
	VBR100PW
	VBR1
CFĻ	add /F13
lew!	
CI-BALLASTED	add /FS23
	add S

100 Series


150w Clear Glass

100w Colored Glass

Max Watts

75w Permaglobe	100w Permaglobe
VBR100DG	VBR200DG
VBR100G	VBR200G
VBR100	VBR200
VBR100P	VBR200P
VBR100PW	VBR200PW
VBR1	VBR2
add /F13	
	add /F22
add /FS23	
add S	add S
add W	add W
add B	add B
Natural, no suffix	

VBR100DG & VBR200DG



VXBR100DG & VXBR200DG




add -3/4

add S

add W

add B

VA100DG & VA200DG





TEL 888 RAB 1000 FAX 888 RAB 1232 www.rabweb.com

157