



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent up to 300 watts. CFL 13 or 22 watts. CFL lamp supplied. Incandescent lamp not supplied.

SPECIFICATIONS

Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in

Color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

UL Listing:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

Colored Globe Maximum Watts:

100 watts

Die Cast Guard:

Supplied with one piece die cast guard with set screw

Hub Size:

3/4" Tapped

Maximum Watts:

150 watts

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color:

Natural

Weight:

3.17

DIMENSIONS

100: 7 ¹ / ₈ "(18.1cm) 200: 8 ¹ / ₈ "(20.6cm)	
100: 4 le"(10.5cm)	100 9 5/8" 24.4 cm 200 11 ¹ / ₄ " 28.6 cm
100:4 1/67110 5cm)	

100: 4 ¹/₈"(10.5cm) **200:** 5 ³/₈"(13.7cm)

ORDERING INFORMATION

Total	Lamp	Lamp		Starting Amps/ Operating Amps				Input	LAMP	Initial	Lan
Watts	Type	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	<u>H</u>
150	A19	Medium	0	0	0	0	0	0	0	0	0

Factory Installed Options
Add suffix to Catalog Number

Note: Specifications may change without notice