



JOB NAME:	
DATE:	
TVDE:	

## **DESCRIPTION**

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent up to 300 watts. CFL 13 or 22 watts. CFL lamp supplied. Incandescent lamp not supplied.

# **SPECIFICATIONS**

### Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in

# Color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

#### Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

#### Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

#### **Colored Globe Maximum Watts:**

100 watts

## **UL Listing:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

#### Die Cast Guard:

Supplied with one piece silver gray die cast guard with set screw

#### **Maximum Watts:**

150 watts

# Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

#### Color:

Silver

# Weight:

3.67

## **DIMENSIONS**

<b>100:</b> 71/8"(18.1cr <b>200:</b> 81/8"(20.6cr	
100: 4 1/a"(10	100 9 5/8" 24.4 cm 200 11 <sup>1</sup> /4" 28.6 cm
<b>100:</b> 4 ½"(10	0.5cm)

200: 5 3/8"(13.7cm)

## ORDERING INFORMATION

Total	Lamp	Lamp	Starting Amps/ Operating Amps					Input	LAMP	Initial	Lan
Watts	Type	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Н
50	A19	Medium	0	0	0	0	0	0	0	0	0

Factory Installed Options
Add suffix to Catalog Number

Note: Specifications may change without notice