

# VXBR100S-3/4

OB NAME:	
DATE:	
TYPE:	

# **DESCRIPTION**

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent up to 300 watts. CFL 13 or 22 watts. CFL lamp supplied. Incandescent lamp not supplied.

# **SPECIFICATIONS**

#### Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in

# Color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

#### Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

## Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

# **Colored Globe Maximum Watts:**

100 watts

No Guard Supplied

#### **UL Listing:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

# **Hub Size:**

3/4" Tapped

# **Maximum Watts:**

150 watts

#### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

#### Color:

Silver

# Weight:

2.84

# ORDERING INFORMATION

Total	Lamp	Lamp			Starting Amps/ Operating Amps					LAMP	Initial	Lamp
Watts	Type	Base	Ballast		120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
150	A19	Medium	0		0	0	0	0	0	0	0	0

Factory Installed Options
Add suffix to Catalog Number