



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent up to 300 watts. CFL 13 or 22 watts. CFL lamp supplied. Incandescent lamp not supplied.

SPECIFICATIONS

Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in color

color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

Colored Globe Maximum Watts:

300 watts

UL Listing:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

Die Cast Guard:

Supplied with one piece white die cast guard with set screw


Maximum Watts:

300 watts Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color: White Weight: 4.67

DIMENSIONS



100: 4 ¹/₈"(10.5cm) **200:** 5 ³/₈"(13.7cm)

ORDERING INFORMATION

Total	Lamp	Lamp		Starting Amps/ Operating Amps				Input	LAMP	Initial	Lamp
Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
300	A19	Medium	0	0	0	0	0	0	0	0	0

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2010 RAB Lighting, Inc.