

VXBR200/F22

JOB NAME: _	
DATE: _	
TYPE:	

DESCRIPTION

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent up to 300 watts. CFL 13 or 22 watts. CFL lamp supplied. Incandescent lamp not supplied.

SPECIFICATIONS

Globes:

Supplied with clear heat resistant glass globes unless otherwise stated. Colored and white glass globes available. Unbreakable RAB Permaglobes available in clear and in

Color. Optional Reflectors:

Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

Socket:

Premium porcelain with 150° C 8" leads attached. Fastened with 2 brass screws.

UL Listing:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90° C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

Wattage:

See catalog number chart for maximum wattage with clear glass, colored glass and Permaglobes.

Ballast Minimum Starting Temperature:

32

Colored Globe Maximum Watts:

200 watts

F22:

Compact Fluorescent 22W

Maximum Watts:

300 watts

No Guard Supplied

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color:

Natural

Weight:

35

ORDERING INFORMATION

Compact Fluorescent Total Lamp Lamp Starting Amps/ Operating Amps Input LAMP Initial Lamp 240V Lamp supplied with fixture Watts Type **Ballast** 120V Watts Lumens Hours 22 22W GX32d-2 NPF 120V 0.45 25 1200 10000 Quad

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice