# WPLED26MS





LED 26W Wallpacks. Patent Pending thermal management system. 100,000 hour L70 lifespan. 5 Year Warranty.

Color: Bronze Weight: 8.0 lbs

Project:	Туре:
Prepared By:	Date:

Driver Info		LED Info	
Type:	Constant Current	Watts:	26W
120V:	0.26A	Color Temp:	5000K (Cool)
208V:	N/A	Color Accuracy:	70 CRI
240V:	N/A	L70 Lifespan:	100,000
277V:	N/A	Lumens:	2,662
Input Watts:	30W	Efficacy:	90 LPW
Efficiency:	88%		

# **Technical Specifications**

## **LED Characteristics**

# Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

#### **Color Consistency:**

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

#### Construction

#### IP Rating:

Ingress Protection rating of IP66 for dust and water.

#### Other

#### **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act

# Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

## **Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

## GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

## Optical

# **BUG Rating:**

B1 U0 G0

# Features

High performance LED light engine

Maintains 70% of initial lumens at 100,000 hours

Weatherproof high temperature silicone gaskets

Superior heat sinking with die cast aluminum housing and external fins

100 up to 277 Volts

5-year warranty

# Ordering Matrix

Family	Watts	Color Temp	Sensor	Surface Plate	Finish	Photocell	Dimming
WPLED							
	<b>26</b> = 26W	= Cool	= No Sensor	= No Surface Plate	= Bronze	= No Photocell	= No Dimming
		Y = Warm	MS = Mini Sensor	S = Surface Plate	W = White	/PC = 120V Button	/D10 = Dimmabl
		N = Neutral				/PCS = 120V Swivel	
						/PC2 = 277V Button	