



LED 26W Wallpacks. Patent Pending thermal management system. 100,000 hour L70 lifespan. 5 Year Warranty.

Color: White

Weight: 8.0 lbs

| | |
|---------------------|--------------|
| Project: | Type: |
| Prepared By: | Date: |

| Driver Info | | LED Info | |
|--------------|------------------|-----------------|-----------------|
| Type: | Constant Current | Watts: | 26W |
| 120V: | 0.26A | Color Temp: | 4000K (Neutral) |
| 208V: | N/A | Color Accuracy: | 83 CRI |
| 240V: | N/A | L70 Lifespan: | 100,000 |
| 277V: | N/A | Lumens: | 2,415 |
| Input Watts: | 30W | Efficacy: | 81 LPW |
| Efficiency: | 88% | | |

Technical Specifications

LED Characteristics

Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

Construction

IP Rating:

Ingress Protection rating of IP66 for dust and water.

Optical

BUG Rating:

B1 U0 G0

Other

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Features

High performance LED light engine

Maintains 70% of initial lumens at 100,000 hours

Weatherproof high temperature silicone gaskets

Superior heat sinking with die cast aluminum housing and external fins

100 up to 277 Volts

5-year warranty

Ordering Matrix

| Family | Watts | Color Temp | Sensor | Surface Plate | Finish | Photocell | Dimming |
|--------|----------|-----------------------------------|---------------------------------|---|-----------------------|---|---------------------------------|
| WPLED | 26 = 26W | = Cool Y = Warm N = Neutral | = No Sensor MS = Mini Sensor | = No Surface Plate S = Surface Plate | = Bronze W = White | = No Photocell /PC = 120V Button /PCS = 120V Swivel /PC2 = 277V Button | = No Dimming /D10 = Dimmable |