



| OB NAME: | |
|----------|--|
| DATE: | |
| TYPE: | |

DESCRIPTION

LED 26 Watt Wallpacks

SPECIFICATIONS

Ambient Temperature:

Suitable for use in 40C ambient

Camporation Title 24:

WPLED complies with California Title 24 building and electrical codes.

Cold Weather Starting:

The minimum starting temperature is -40¡C

Color Accuracy:

66 CRI

Color Stability:

RAB LED products significantly exceed Energy Star Requirements for Chromatic Stability during LM-80 Testing.

Color Temperature (Nominal CCT):

5169 K (Daylight)

Color Uniformity:

RABÕs range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

Equivalency:

The WPLED26 is Equivalent in delivered lumens to a 175W Metal Halide Wallpack.

Fixture Efficacy:

61 Lumens per Watt

Finish:

Chip and fade resistant polyester powder coat finish.

HID Replacement Range:

The WPLED26 can be used to replace 150 - 200W Metal Halide Wallpacks based on delivered lumens.

Heatsink:

Cast aluminum thermal management system for optimal heat sinking. The LPACK is designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

LED Light Engine:

Multi-chip 26W high output long life LED Driver: Constant Current, 720mA, Class 2, 6 KV Surge Protection, 100V-277V, 50-60 Hz, 100-240V: .4 Amps

Patents:

The WPLED design is protected by U.S. PATENT D608,040 and patents pending in the U.S., Canada, China, Taiwan and Mexico.


COIO

White

Weight:

7.5

DIMENSIONS



ORDERING INFORMATION

| LED Lamp supplied with fixture | Total Watts | Lamp Type | Lamp Base | Ballast | Starting 120V | Amps/ Op 208V | erating A | mps 277V | Input Watts | LAMP ANSI | Initial Lumens | Lamp Hours |
|--|--|--------------|--------------|------------------|-----------------------------|------------------|-----------|-------------|----------------|--------------|-------------------|---------------|
| | 26 | LED | Therm al | Constant Current | .4 A/.4 A | .4 A/.4 A | .4 A/.4 A | .4 A/.4 A | 30.2 | N/A | 1816 | 50000 |
| Factory Installed Options Add suffix to Catalog Number | Photocontrol for 277 小作种 (2) nk | | | | Photocontrol for 120V (/PC) | | | | | | | |

Note: Specifications may change without notice