



OB NAME:	
DATE:	
TYPE:	

## **DESCRIPTION**

LED 26 Watt Wallpacks

## **SPECIFICATIONS**

# **Ambient Temperature:**

Suitable for use in 40C ambient

## Camporation Title 24:

WPLED complies with California Title 24 building and electrical codes.

## **Cold Weather Starting:**

The minimum starting temperature is -40¡C

# **Color Accuracy:**

66 CRI

## **Color Stability:**

RAB LED products significantly exceed Energy Star Requirements for Chromatic Stability during LM-80 Testing.

# **Color Temperature (Nominal CCT):**

5169 K (Daylight)

# **Color Uniformity:**

RABÕs range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

#### Equivalency:

The WPLED26 is Equivalent in delivered lumens to a 175W Metal Halide Wallpack.

### **Fixture Efficacy:**

61 Lumens per Watt

#### Finish:

Chip and fade resistant polyester powder coat finish.

#### **HID Replacement Range:**

The WPLED26 can be used to replace 150 - 200W Metal Halide Wallpacks based on delivered lumens.

#### Heatsink:

Cast aluminum thermal management system for optimal heat sinking. The LPACK is designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

# **LED Light Engine:**

Multi-chip 26W high output long life LED Driver: Constant Current, 720mA, Class 2, 6 KV Surge Protection, 100V-277V, 50-60 Hz, 100-240V: .4 Amps

#### Patents:

The WPLED design is protected by U.S. PATENT D608,040 and patents pending in the U.S., Canada, China, Taiwan and Mexico.


#### COIO

White

### Weight:

7.5

## **DIMENSIONS**



#### ORDERING INFORMATION

LED	Total	Lamp	Lamp		Starting Amps/ Operating Amps				Input	LAMP	Initial	Lamp
Lamp supplied with fixture	Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
	26	LED	Therm al	Constant Current	.4 A/.4 A	A .4 A/.4 A	.4 A/.4 A	.4 A/.4 A	30.2	N/A	1816	50000
Factory Installed Options Add suffix to Catalog Number	Photocontrol for 277小句句(2) nk				Photocontrol for 120V (/PC)							

Note: Specifications may change without notice