# WP1F42W/PC

Compact Wallpack. UV stabilized, vandal resistant prismatic polycarbonate refractor. Lamp supplied.

#### Lamp Info **Ballast Info**

Type:	42W Triple	Type:	Elec HPF QT
Watts:	42	120V:	0.38
Shape/Size:	N/A	208V:	0.3
Base:	N/A	240V:	0.2
ANSI:	N/A	277V:	0.17
Hours:	12,000	Input Watts:	46W
Lamp Lumens:	3,200	Efficiency:	91%
Efficacy:	70 LPW		

# **Technical Specifications**

# **UL Listing:**

Suitable for wet locations. HID fixtures can be wired with 90 C supply wiring if supply wires are routed 3" away from the ballast.

#### Housing:

Die cast aluminum, 1/2" NPS tapped top, both sides and back for conduit or photocontrol. Hinged refractor. Continuous one piece silicone rubber gasket.

#### Reflector:

Semi-Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

#### Finish:

Chip and fade resistant polyester powder coating.

#### Photocell:

Button Photocell installed and wired for 120V

# **Conduit Openings:**

Top, side, and back

#### Template:

Drilling template for easy wall box mounting

#### Patents:

Pat. D440,683

# **Ballast Minimum Starting Temperature:**

0 Deg F

# **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by IBEW Local 3

# **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

# Weight: 5.7 lbs 8 1/2" 21.6 cm 8 8 5/8 22 cm

# Recovery Act (ARRA) Compliant:

Color: White

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods--Buy American Act-- Construction Materials (October 2010)

# **Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

# **GSA Schedule:**

This product is suitable for listing on the GSA Schedule of the US General Services in accordance with FAR Subpart 25.4