



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Mid sized wallpack. All aluminum precision die cast contruction with tempered glass refractor. Lamp supplied.

SPECIFICATIONS

Cutoff Lens:

Tempered glass.

Finish:

Chip and fade resistant polyester powder coating.

Housing:

Die cast aluminum, 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame. Continuous silicone rubber gasket.

Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

Color:

White

Refractor:

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws


Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts

Weight:


36

DIMENSIONS



PHOTOMETRIC

150w HPS @10' Mounting Height



	Multiples
Mounti Height	ng Multiplier
8'	1.6
10'	1.0
12'	.7
16'	.4
20'	.25

1	Multiplier					
	Watts	HPS	MH	CFL		
	175		.9			
	150PS		.9			
	150	1.0	.8			
	125PS		.7			
	100	.6	.6			
	70	.4	.4			
	42			.2		
	84			.4		

ORDERING INFORMATION

High Pressure Sodium Total Lamp Lamp Starting Amps/ Operating Amps Input LAMP Initial Lamp Watts **Ballast** 120V 208V 240V Lamp supplied with fixture Type Base 70 ED17 Medium HX-HPF QT .8/.9 .5/.5 S62 6400 24000

Factory Installed Options Add suffix to Catalog Number

Tamperproof screws (/TP)
Swivel Photocontrol (/PCS)
Single fusing for 120 and 277 volt (/F)

Double fusing for 208 and 240 volt (/FF) Button Photocontrol for 208 - 277 volt (/PC2) Button Photocontrol (/PC)

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2010 RAB Lighting, Inc.