

TRP/QSP/RDI

Architectural HID/CFL Wallpacks

Architectural wallpack stylish shapes with molded lines to accentuate building architecture. Provides excellent illumination in PSMH and CFL systems.

- Three distributions: (see below for restrictions) FT - forward throw for area lighting, WT - wide lateral throw for maximum spacing and UD - Up/Down accent distribution
- Die cast aluminum housing and door
- Different powder coat finishes available

- Tempered, impact-resistant, clear glass lens
- Full cut-off, dark sky, neighbor friendly
- HID color temperature 4000K
- CFL color temperature 3500K
- HID lamps are medium base
- UL 1598 listed for use in wet locations
- Full cut-off, dark sky, neighbor friendly
- Lamps included for HID and CFL geometric wallpacks



WALLPACKS

ORDERING INFORMATION

SERIES	WATTAGE/SOURCE/VOLTAGE	DISTRIBUTION	FINISH	OPTIONS
TRP Trapezoid	PULSE START¹	FT² Forward Throw	DB Dark Bronze	QST⁶ Time delay quartz standby system energizes quartz socket when main lamp does not strike (HID only)
RDI Radius	150P8 150W PS Quad	WT² Wide Throw	PREMIUM COLORS	EM Double contact bayonet socket only for use with 120V remote power (generator by others)
QSP Quarter Sphere	100P8 100W PS Quad	UD⁷ Up/Down		EM12 Two-pin 12V socket for MR11/MR16 lamps (backup power by others)
	70P8 70W PS Quad			PC(X)^{4,5} Button photocontrol, Specify voltage 1-120V, 2-208V, 3-240V, 4-277V
	50P9 50W PS Quad 120/277V			BOC(X)^{4,5} 0° battery backup for one CFL lamp, provides 90 minutes backup power, specify 1-120V or 4-277V
	CFL¹			
	26F8 26 CFL Quad			
	32F8 32 CFL Quad			
	42F8 42 CFL Quad		BL Black	
	52F8³ 2x26 CFL Quad		GR Gray	
	64F8³ 2x32 CFL Quad		WH White	
	84F8³ 2x42 CFL Quad		PS Platinum	
			CC Custom Color	

- 1 Single ballast standard, contact factory for double ballast option
- 2 IDA approved
- 3 Available in WT distribution only
- 4 BOC option not available with UD, up/down distribution
- 5 -20C BBU option available, consult factory. For 52/64/84 versions, battery operates one lamp
- 6 100w D.C. bayonet lamp included
- 7 Available in RDI and RTP only

ACCESSORIES/REPLACEMENT PARTS - Order Separately

Family	Catalog Number	Description
QSP/RDI/RTP/TRP	E-BUB-P42-35GC	42w CFL lamp, 3500K
QSP/RDI/RTP/TRP	E-BAL-CF26E-ADV	CF Ballast (26-52w)

DIMENSIONS

