

7"/11"/15" Round

Ceiling and Wall Mount

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp & CRI	Watt	Lumens	Finish	
FM-07RN 7"	930 3000K - 90	15W	1100	BN Brushed Nickel	
	935 3500K - 90	15W	1100	BZ Bronze	
FM-11RN 11"	930 3000K - 90	20W	1525	WT White	
	935 3500K - 90	20W	1525		
FM-15RN 15"	930 3000K - 90	28W	2550		
	935 3500K - 90	28W	2550		

Example: FM-07RN-930-BN

DESCRIPTION

Ultra-slim flush mount that uses edge-lit technology and a translucent diffuser for uniform illumination without shadows or hotspots.

FEATURES

- Multiple LED array for uniform illumination
- Driver installed within the Junction Box, driver dimension: 2.25" dia x 1" deep
- 5 year warranty



Construction: Aluminum with translucent diffuser

Power: 15W, 28W, 20W
Input: 120 VAC, 50/60Hz

Dimming: ELV: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED

Lens: Translucent acrylic diffuser

Rated Life: 50000 Hours

Mounting: Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be

mounted on ceiling or wall in all orientations

Finish: Electrostatically Powder Coated:White, Electrostatically

Powder Coated::Bronze, Electrostatically Powder

Coated:::Brushed Nickel


Operating Temp: $-4^{\circ}F$ to $104^{\circ}F$ (-20°C to $40^{\circ}C$)

Standards: UL, cUL, Damp Location Listed, Energy Star 2.0, Title 24

JA8-2019 Compliant, ADA



FINISHES:



LINE DRAWING:

