

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Endurance™ Brick Lights Louver Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-5205 120 VAC	3000K 90	45	ABK Architectural Black ABZ Architectural Bronze AGH Architectural Graphite AWT Architectural White

Example: **WL-5205-30-ABK**

DESCRIPTION

Designed for integration into brick walls or vertical risers. The energy-efficient Endurance LED Brick Light features a die-cast aluminum housing and integrated LED light engine with a heat resistant opal glass diffuser for a glare-free even spread of light, making outdoor areas safer and more secure.

FEATURES


- Glare controlling die-casted aluminum louver
- Factory sealed LED light engine
- 5 year warranty

SPECIFICATIONS


Construction:	Die-cast aluminum (K-Alloy)
Power:	5.5W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
Rated Life:	80000 Hours
Mounting:	Mortar into masonry, screw into wood walls, or retrofit into existing brick light installations, Can be mounted on wall vertically or horizontally
Cut Out:	3 1/4" x 8"
Finish:	Electrostatically Powder Coated Architectural White, Electrostatically Powder Coated Architectural Bronze, Electrostatically Powder Coated Architectural Graphite, Electrostatically Powder Coated Architectural Black
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA



FINISHES



LINE DRAWING



REPLACEMENT PARTS

- 5205-COV-AWT - Louvered Cover Plate AWT
- 5005-PLATE - Mnt Plate for Light Engine
- 5205-COV-AGH - Louvered Cover Plate AGH
- 5205-COV-ABZ - Louvered Cover Plate ABZ
- 5205-COV-ABK - Louvered Cover Plate ABK