

Folsom

Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
WS-W23610 10"	3000K 90	BZ Bronze	6.5W	630	120	Yes

Example: WS-W23610-BZ

•For 277V special order, add an "F" before the finish: WS-W23610F-BZ

For custom requests please contact customs@waclighting.com

DESCRIPTION

Die-cast aluminum forged into stripes encasing an inner etched opal glass create a unique design suitable for many outdoor commercial and residential applications. Folsom is availablein two finish options, and two sizes.

FEATURES

- Title 24 may not be available for all finishes, check for availability
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10%
Rated Life: 50000 Hours

Mounting: Can be mounted on wall in all orientations
Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum with acrylic diffuser



FINISHES:




Bronze

LINE DRAWING:

REPLACEMENT PARTS

RPL-GLA-23610-01 - Outer glass for WS-W23610 RPL-GLA-23610-02 - Inner glass for WS-W23610





Folsom

Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
WS-W23614 14"	3000K 90	BZ Bronze	12W	965	163	Yes

Example: WS-W23614-BZ

•For 277V special order, add an "F" before the finish: WS-W23614F-BZ

For custom requests please contact customs@waclighting.com

DESCRIPTION

Die-cast aluminum forged into stripes encasing an inner etched opal glass create a unique design suitable for many outdoor commercial and residential applications. Folsom is availablein two finish options, and two sizes.

FEATURES

- Title 24 may not be available for all finishes, check for availability
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10%
Rated Life: 50000 Hours

Mounting: Can be mounted on wall in all orientations
Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum with acrylic diffuser

FINISHES:



Bronze

LINE DRAWING:

REPLACEMENT PARTS

RPL-GLA-23614-01 - Outer glass for WS-W23614 RPL-GLA-23614-02 - Inner glass for WS-W23614

