WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Rubix

Single & Double Wall Mount 3000K

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
WS-W2504 Single WS-W2505 Double	3000K 90 3000K 90	16W 30W	750 1400	AL Brushed Aluminum BK Black BZ Bronze GH Graphite WT White

Example: WS-W2504-AL

DESCRIPTION

Available in single and twin light configurations, this die-cast aluminum LED wall luminaire is Wet Location listed for a broad range of exterior lighting applications. Designed with asquare profile, this version of Rubix mounts upwards or downwards.

FEATURES

- 2504 Single, 2505 Double
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS


Construction:	Die-cast Aluminum	
Power:	30W, 16W	
Input:	120-277 VAC, 50/60Hz	
Dimming:	ELV: 100-15% , 0-10V: 100-10%	
Light Source:	Integrated LED	
Rated Life:	70000 Hours	
Mounting:	Mounts directly to junction box, Can be mounted on wall in all orientations	
Finish:	Electrostatically Powder Coated: White, Graphite, Bronze, Black, Brushed Aluminum -40°F to 122°F (-40°C to 50°C)	
Operating Temp:		
Standards:	ETL, cETL, Wet Location Listed, IP65, Title 24 JA8-2019 Compliant	

FINISHES:



Aluminum

LINE DRAWING:



WS-W2504, WS-W2505