

Rubix

Wall Mount 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Watt	Lumens	Finish	
WS-W2509 Single WS-W2510 Double	3000K 90 3000K 90	16W 30W	805 1385	AL Brushed Aluminum BK Black BZ Bronze GH Graphite WT White	

Example: WS-W2509-AL

DESCRIPTION

Available in single and twin light configurations, this die-cast aluminum LED wall luminaire is Wet Location listed for a broad range of exterior lighting applications. Designed with asquare profile, this version of Rubix mounts upwards or downwards.

FEATURES

- 2509 Single, 2510 Double
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast Aluminum

Power: 30W, 16W

Input: 120-277 VAC, 50/60Hz

Dimming: ELV: 100-15%, 0-10V: 100-10%

Light Source: Integrated LED Rated Life: 70000 Hours

Mounting: Mounts directly to junction box, Can be mounted on wall

in all orientations

Finish: Electrostatically Powder Coated: White, Graphite, Bronze,

Black, Brushed Aluminum

Operating Temp: $-40^{\circ}F$ to $122^{\circ}F$ ($-40^{\circ}C$ to $50^{\circ}C$)

Standards: UL, cUL, Wet Location Listed, IP65, Title 24 JA8-2019

Compliant, ADA



FINISHES:



LINE DRAWING:

