

Tube

Single & Double Wall Mount 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Watt	Lumens	Finish	
WS-W2604 Double WS-W2605 Single	3000K 90 3000K 90	30W 16W	1750 800	AL Brushed Aluminum BK Black BZ Bronze GH Graphite WT White	

Example: WS-W2604-AL

DESCRIPTION

A simple sconce with endless possibilities. This cylindrical wall luminaire delivers powerful lumen output, either upwards or downwards, or a combination of both, depending on the configuration and application. Built to last with die-cast aluminum construction and designed with no visible hardware, this low profile highly versatile Tube is perfect for your exterior

FEATURES

- Title 24 may not be available for all finishes, check for availability
- 2605 Single, 2604 Double
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast Aluminum

Power: 16W, 30W

Input: 120-277 VAC, 50/60Hz

Dimming: ELV: 100-15%, 0-10V: 100-10%

Light Source: Integrated LED Rated Life: 70000 Hours

Mounting: Mounts directly to junction box, Can be mounted on wall

in all orientations

Finish: Electrostatically Powder Coated: White, Graphite, Bronze,

Black, Brushed Aluminum


Operating Temp: -40°F to 122°F (-40°C to 50°C)

Standards: ETL, cETL, Wet Location Listed, IP65, Title 24 JA8-2019

Compliant



FINISHES:



LINE DRAWING:

