

Caliber

Outdoor Wall Sconce 3000K

Tixture Type.	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-W36610 10"	3000K 90	AL Brushed Aluminum BK Black BZ Bronze	11W	735	560

Example: WS-W36610-BZ

For custom requests please contact customs@waclighting.com

DESCRIPTION

Light projection tuned with precision, Caliber is a discrete cylinder with minimal mounting hardware. Available in a single or double light configuration which can be mounted bothvertically and horizontally. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Discrete cylinder with minimal mounting hardware
- Weather-resistant powder coated finish
- WS-W36614 is Up & down light, WS-W36610 is one direction
- Light engine is factory sealed for maximum protection from the elements
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120-277 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 72000 Hours

Mounting: Can be mounted on wall vertically or horizontally

Standards: ETL, cETL,IP65

Wet Location Listed


Construction: Aluminum hardware with lens diffuser



FINISHES:



LINE DRAWING:



WS-W36610



Caliber

Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-W36614 14"	3000K 90	AL Brushed Aluminum BK Black BZ Bronze	21W	1500	1140

Example: WS-W36614-BZ

For custom requests please contact customs@waclighting.com

DESCRIPTION

Light projection tuned with precision, Caliber is a discrete cylinder with minimal mounting hardware. Available in a single or double light configuration which can be mounted bothvertically and horizontally. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Discrete cylinder with minimal mounting hardware
- Weather-resistant powder coated finish
- WS-W36614 is Up & down light, WS-W36610 is one direction
- Light engine is factory sealed for maximum protection from the elements
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120-277 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 72000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,IP65

Wet Location Listed


Construction: Aluminum hardware with lens diffuser



FINISHES:



LINE DRAWING:



WS-W36614